

Newspaper Vending Machine

The **PX1** (VA) is a fully automated vending machine for newspapers and magazines, a single copy dispenser. After paying the amount presented on the LCD, the machine ejects the product immediately. Paying is also possible by SmartCard.

After inserting the OperatorCard the data will be exchanged between card and machine and the frontdoor is opened. Now the operator has access to load the new products very comfortable.

The **PX1** is battery and solar powered (option).

The attractive and robust design keeps vandals away.

PX1 is a result of an intensive development process with the long term experience with the famous machine J1000.



Benefits

- Simple operation and **RFID option**
- LCD for continuous price indication
- In- / Outdoor application, mobility
- Comfortable front door loading
- Hybrid operation: full- or semiautomat (option)
- SMS and NFC payment (option)
- Separate controllable access to cash register (option)
- Easy maintenance by changing assemblies
- Daten transfer, change of price and door control by OperatorCard
- Full compatibility to WinfovendPro, the management software package with interface to MS Access database or MS SQL server (option)



Mechanics

Dimension:

Type CH 1100 x 480 x 480 mm (Height x Depth x Width)

Type Globe 1100 x 580 x 480 mm (Height x Depth x Width)

Weight approx. 61 kg (without products)

Housing made of powder coated galvanized metal sheets

Transparent products made of UV resistant Polycarbonate (PC)

Load volume approx. 650 mm

Fixation at point of sales (POS) by chain (option)

Elektronics

Electronic payment module **ZM10** for ServiceCards, SubscriptionCards (option) and coins up to $\varnothing 32$ mm.

Compact module with integrated LCD and escrow

PC interface for programming.

Vending Controller integrated in the **ZM10**.

RFIDReader (only with power supply)

Power Supply

Battery 12V / 7Ah solar charged (option)

Power supply 230V AC (option)



josTTech GmbH

Haemmerli 6

CH-8855 Wangen

info@josTTech.ch - www.josTTech.ch

Tel +41 55 460 22 25 - Fax +41 55 460 22 26

Future developments can lead to changes in specifications and pricing at any time

